OceanStor N8500 Clustered NAS Storage System





OceanStor N8500

Huawei's OceanStor N8500 clustered NAS storage system is a leading unified storage platform oriented to high-end and medium-range applications. It meets the service requirements of telecommunications operators, digital media, high-performance computing, governmental entities, and educational and scientific research industries. It provides high performance, high expansion, effective data management, and unified storage.

Highlights

High Performance

- Leading performance: The storage system provides top performance in the SPECsfs2008 benchmark. When the NFS protocol is used, performance reaches 3,064,602 OPS.
- Cluster architecture: Multinode Active-Active cluster technology is used. In the cluster, all nodes work in a cooperative manner to implement concurrent data access.
- Globally shared storage: All nodes can access the same storage at the same time. The engine node provides the load balancing function. After load balancing is implemented, the load caused by hot-spot data access is evenly distributed to all nodes. This improves access efficiency of hot-spot data.
- Highly reliable architecture: Redundant components prevent single points of failure. Software technologies such as data coffer and file system mirror further improve system reliability.

Scalability

- Expansible engine node: Engine nodes can be smoothly expanded online to 24 nodes. System performance improves with the addition of engine nodes.
- Expansible storage capacity: Storage capacity can be expanded to 15 PB.
- File system capability: Maximum file system space is 256 TB. Each file system supports up to 1,000,000,000 files.

Efficiency

 Dynamic Storage Tiering (DST): Bidirectional dynamic migration is implemented between different storage media based on file access frequency and time policy. It is transparent to applications and reduces enterprise CAPEX.

- File system mirror function: In certain storage systems, a file system mirror can be set to store multiple data file systems and improve online data reliability.
- Soft/hard quota management: This implements flexible user space allocation and use.
- Domain management: AD/NIS/LDAP is supported.
- Backup solution: The Symantec NetBackup Client can be embedded in the NAS engine node to optimize backup performance and shorten the backup window.

Convergence

- Unified protocols: Unified storage refers to unified storage of the SAN
 or NAS storage protocol. Certain storage systems support structured
 and unstructured data storage. Multiple storage network protocols
 such as iSCSI, FC, FCoE, NFS, CIFS, HTTP, and FTP are supported.
- Unified management: A simple graphical interface provides a unified way to manage files and block data services. A wizard configuration mode helps complete configurations easily.
- Device monitoring: The graphical management interface provides real-time/historical performance measurement and supports multiple alarm modes such as audible alarms, visual alarms, and email alarms. A device's operating status can be monitored at any time.
- File-level data protection technology: Snapshot, snapshot recovery, and remote replication functions at the file system level provide multilevel data protection.
- Block-level data protection technology: Smart Cache dynamic data cache technology and value-added features such as LUN-based snapshot, copy, and synchronous/asynchronous remote replication are provided for block-level data.

OceanStor N8500 Clustered NAS Storage System



Technical Specifications

	Model	N8500
Hardware Specific	cations	
Architecture		Multinode Active-Active cluster architecture
Number of nodes		2 – 24
Cache/node		Basic Version: 16 GB
		Standard Version: 24 GB
		Enterprise Version: 48 GB
		Enhanced Version: 96 GB up to 192 GB
GE ports/node		Standard configuration: 4 x GE, up to 16 x GE
10 GE ports/node		Up to 6 x 10 GE
Disk type		SSD, FC, SAS, SATA, NL-SAS
Physical storage capacity		Dynamically expandable up to 15 PB
Software Features	S	
RAID levels		0, 1, 3, 5, 6, 10, 50
File system size		Dynamically expandable up to 256 TB
Maximum number of snapshots		512 (per file system)
Storage network protocols		FC, FCoE, ISCSI, NFS, CIFS, FTP, HTTP
Access control		NIS, Microsoft Active Directory, LDAP
Other protocols		NDMP, SNMP, NTP,SMI-S
Value-added functions		DST, Snapshot, Mirror, Quota, Replication,
		SmartCache (dynamic data cache technology), embedded Symantec NetBackup Client, De-Duplication, Compression,
		Anti-Virus, WORM, HyperThin (thin provisioning), HyperImage (snapshot), HyperCopy (LUN copy),
		HyperClone (split mirror), and HyperMirror (synchronous/asynchronous remote replication)
Quota		NFS/CIFS soft/hard quota management
Management mode		GUI, CLI
Compatible operating systems		Windows, Linux, Mac OS, Solaris, AIX, and HP-UX
Fault alarm modes		Email, SNMP, and Syslog
Physical Specificat	tions	
Power supply		AC: 100 V to 127 V/ 200 V to 240V
		DC: -48 V to -60 V
Power consumption	Engine	≤ 830 W (dual-node cluster)
	Storage unit	Controller enclosure: ≤ 830 W; Disk enclosure: ≤ 550 W
Dimensions (H x W x D)	Engine	4U, 175 mm x 446 mm x 502 mm (dual-node cluster)
	Storage unit	2U, Controller enclosure: 86.1 mm x 446 mm x 582 mm
		4U, Controller enclosure: 175 mm x 446 mm x 502 mm
		2U, Disk enclosure: 86.1 mm x 446 mm x 412 mm
		4U, Disk enclosure: 175 mm x 446 mm x 412 mm
	Cabinet	42U, 205 cm x 57.5 cm x 118 cm
Weight	Engine	Dual-node clustered NAS engine: ≤ 43.6 kg
	Storage unit (in full configuration)	2U, Controller enclosure ≤29.9 kg/enclosure
		4U, Controller enclosure ≤43.6 kg/enclosure
		2U, Disk enclosure ≤26.5 kg/ enclosure; 4U, Disk enclosure ≤42.64 kg/enclosure
Operating temperature		5°C to 40°C
Operating humidity		5% RH to 90% RH

Copyright $\ensuremath{@}$ Huawei Technologies Co., Ltd. 2013. All rights reserved.

THIS DOCUMENT IS FOR INFORMATION PURPOSE ONLY, AND DOES NOT CONSTITUTE ANY KIND OF WARRANTIES.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base Bantian Longgang Shenzhen 518129, P.R. China Tel: +86-755-28780808