

HUAWEI VP9630 MCU



HUAWEI VP9630 is a cutting-edge MCU with high cost-effectiveness, flexible ports utilization and high scalability. It is an industry-leading MCU to support up to 4K universal transcoding. Interoperability with various types of endpoints intelligently, VP9630 delivers users an ultimate videoconferencing experience

High performance and universal transcoding bring an ultimate experience

The industry-leading MCU supporting 4K(3840×2160) universal transcoding provides an ultimate videoconferencing experience for participants

H.265 and H.264 High Profile saves bandwidth by 50%

AAC-LD realizes CD-quality audio effect and three-channel brings sound localization

Intelligent transcoding for content sharing across different types of devices

Easy to Deploy and Use

Multiple Methods for conference initiation, such as HUAWEI SiteCall™, Ad hoc, and web-based scheduling

Plenty of conference control functions, including Automatic Continuous Presence, Voice Activation, Chair control, DTMF Control, Audio/Video IVR, H.239 Content Sharing Token, and FECC

Secure, Reliable and Powerful QoS

H.264 SVC and SEC 3.0 ensure smooth videoconferences even if the packet loss is up to 20%

Dynamic jitter buffer up to 1000 ms ensures conference quality

IRC™ provides the best conference experience with low network bandwidth

Ensures conference data security via H.235 (AES256), SRTP/TLS(AES256) and SSH

MCU, Power, Network interface and Chipset hot spare

Standard-based, Open Scalable

Supports multilevel cascading, multichannel cascading and conference recording

Standard-based and open: Supports H.323, SIP and convergence conference of Telepresence, HD/SD endpoints, mobile devices and audio endpoints

SOAP-based API for integration with third-party systems

Maximizes resource utilization and improves ROI by flexible resource allocation

HUAWEI VP9630 Specifications

Video Standards and Protocols
ITU-T H.265, H.264, H.264 HP, H.264 SVC, H.263, H.263+, H.263++ ITU-T H.239, BFCP
People Video Resolution
Resolution: QCIF, CIF, 4CIF, 288p, 360p, 720p, 1080p, 4K(3840×2160) Video Frame Rate: 25fps, 30fps, 50fps, 60fps 16:9 and 4:3 aspect ratio
Content Video Resolution
Coding/Decoding resolution: QCIF, QVGA, CIF, VGA, 4CIF, SVGA(800×600), XGA(1024×768), SXGA+(1600×1200), 288P(512×288), 360P(640×360), 396P(704×400), 720P, 1080P, 4K(3840×2160) Decoding resolution: WXGA, SXGA, XGA+, 1920×1200 Content adaptation
Audio Standards and Protocols
AAC-LD, AAC-LC, G.722.1*, G.722.1C*, G.711a/u, G.722, G.728, G.729A, G.729AB, G.719, iLBC, Opus Three-channel Stereo
Other Supported Standards
H.221, H.225, H.235, H.242, H.243, H.245, H.281, H.283, FECC, RFC2833, DTMF, SRTP, TLS, T.140, NTP
Network
Standards and protocols: ITU-T H.323, IETF SIP Network standards: IPv6/IPv4, TCP/IP, FTP/FTPS, RTP, RTCP, HTTP/HTTPS, SNMP, TELNET, SSH, DNS/DDNS Bandwidth for one port: 64Kbps~8Mbps Network Interfaces: <ul style="list-style-type: none">• GE, 1000 Mb, RJ45• FE, 100 Mb, RJ45• RS232, RJ45• SFP, Gigabit optical fiber interface
Line Types: IP
Management Tools
Support SSH Remote upgrade Resource statistic Hardware diagnosis Support CDR (Call Detail Record) Data export and import Support Conference configuration template Status monitor
Physical dimensions
Net Dimension: 442mm(W) × 450mm(D) × 86.1mm(H), 2U Package Dimension: 780mm(W) × 580mm(D) × 260mm(H), 2U Net weight: 16 kg Package Weight: 22 kg AC input: 100 ~ 240V 50/60Hz Max power consumption: 400W
System Capacity
Up to 4 H.265 4K ports in CP or 16 H.264 1080p60 ports in CP or 32 H.264 1080p30 ports in CP or 64 H.264 720p30 ports in CP Additional audio ports: as many as 1080p30 ports

*: G.722.1/G.722.1C, licensed from Polycom®

enterprise.huawei.com

Copyright©2018 Huawei Technologies Co., Ltd. All rights reserved.

IP QoS
DiffServ (DSCP), IP Precedence, ARQ SEC™3.0 (Super Error Concealment) IRC™ (Adaptability Intelligent Rate Control) Auto adaptation enabling Priority settings of QoS
Security
Conference password HTTPS ensures the safety for Web accessing H.235 (AES256)and SRTP/TLS(AES256) encryption
Approval and Compliance
CE, WEEE, RoHS, REACH, FCC, UL, VCCI-A, GOST, C-TICK
Highlights
Universal transcoding for Telepresence CP on each port, Up to 24 CP Auto Continuous Presence Flexible ports 48 modes of Continuous Presence Up to 5-level multichannel cascading Ad hoc and Audio/Video IVR HUAWEI SiteCall™ Schedule conferences via Web and Outlook Email notification URI dialing Plenty of conference control functions Chair control Endpoint control via DTMF Message overlay Mute video Support camera control Support content lock Support video source lock Intelligent negotiation: Best utilization of endpoint's ability IVR Language: English, French, German, Spanish, Russian, Japanese, Chinese Web UI Language: English, Chinese
Operating Environment
Operating temperature: -5°C ~ 45°C Relative humidity: 10% ~ 95% (Non - Condensing) Air pressure: 63 ~ 106KPa Reliability MTBF: >100,000 hours MTTR: < 0.5 hour