



**7903X IP Phone Expansion Module  
V200R003**

# **Product Overview**

**Issue**        **02**  
**Date**        **2015-05-30**

**Copyright © Huawei Technologies Co., Ltd. 2017. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

## **Trademarks and Permissions**



and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

## **Notice**

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

## **Huawei Technologies Co., Ltd.**

Address: Huawei Industrial Base  
Bantian, Longgang  
Shenzhen 518129  
People's Republic of China

Website: <http://enterprise.huawei.com>

# Contents

---

<b>1 Product Positioning and Highlights.....</b>	<b>1</b>
<b>2 Technical Specifications .....</b>	<b>3</b>

# 1 Product Positioning and Highlights

---

7903X is a multi-functional IP phone expansion module. It is used with 7950 to provide various functions, including speed dial, phone lock, phone sleep, and contact group. With a single 7903X, 7950 increases the number of programmable buttons to 40 and provides optimized viewing through the 5-inch color LCD screen. 7903X helps users use 7950 more efficiently with better user experience.

Product model: 7903X

Product highlights:

- 5-inch , 480 x 800 pixel color LCD screen with backlight
- 20 programmable buttons with dual-color LED indicators, and two page buttons with monochrome LED indicators
- A second page button that provides access to additional 20 programmable buttons (for a total of 40 buttons)
- Only one 7903X connected to each 7950 when powered by 7950
- Up to three 7903Xs connected to each 7950 when powered by external power supply
- Icons displayed for phone lock and sleep functions
- Dual-color LED indicators to tell different line states of contacts
- Multi-language support
- A rich set of functions including speed dial, phone lock, and phone sleep.

[Figure 1-1](#) shows the appearance of 7903X.



# 2 Technical Specifications

Table 2-1 lists the specifications of 7903X.

**Table 2-1** specifications

Category	Parameter	
IP phone support	7950	
Screen	5-inch, 480 x 800 pixel, color LCD screen	
Language display	Arabic, Chinese (simplified and traditional), English, French, Portuguese, Arabic, Trurkish, Russian, and Spanish	
Buttons	20 programmable buttons and two page buttons	
Maximum number of pages	2 pages	
Maximum number of programmable buttons	40	
Number of expansion modules that can be used	<ul style="list-style-type: none"><li>Powered by 7950: only 1 expansion module</li><li>Powered by external power supply: up to 3 expansion modules</li></ul>	
Functions	Busy Lamp Field (BLF), speed dial, XML application, phone lock, contact group, sleep, Call Forward, DND, Call Park, Pickup, Group Pickup, Hunt Group, Paging	
Electrical features	Power adapter	Input: 100 to 240 V AC Output: 5 V DC, 2 A Support for China, Europe, America, Britain, Brazil, and Australia standards
	Power consumption (approx.)	3 W
Environmental requirements	Operating temperature	0°C to 45°C
	Operating humidity	10% to 95%
	Storage temperature	-25°C to +70°C

Category	Parameter	
	Storage humidity	10% to 95%
Physical features	Dimensions	130 mm x 208 mm x 67.5 mm
	Weight(approx.)	0.41kg
	Installation mode	Desktop installation