

# Rectifier Module

R4850G2



## Introduction

R4850G2 is a 3000W, 96% efficiency, digital controlled high power density rectifier.

It converts input voltage ranges between 85 to 300 Vac into 42 to 58 Vdc adjustable output voltage.

With state-of-the-art technologies, the online-swappable rectifier module supports walk-in start, low noise operation and multiple functions on real-time state management.



Overview of R4850G2

## Features

- **High efficiency:** 96%
- **Wide operating temperature range:**  $-40^{\circ}\text{C}$  to  $+75^{\circ}\text{C}$  (full output up to  $55^{\circ}\text{C}$ )
- **Wide input voltage range:** 85 to 300 Vac
- Total harmonic distortion (THD) :  $\leq 5\%$
- **Hot-swappable** rectifier
- **Digital control**
- **CAN communication**
- Adjustable voltage and current
- **TUV,CE,UL,FCC,CB** certifications




Front view of R4850G2

## Scenarios


- Access network
- Transmission network
- Communication network of enterprises




## Feature Curve




Output Feature Curve



Output Power Vs Input Voltage Curve




Energy Efficiency Curve



Output Power Vs Temperature curve

## Dimension Drawings



# Specifications

Product Type		R4850G2
Basic Specifications	Dimension	105 mm(W) × 281 mm(D) × 40.8 mm(H)
	Weight	≤ 2.0 kg
	Cooling	Forced air cooling (Built-in fan)
Input Feature	Input Voltage	85 to 300 Vac
	AC Input Mode	220 Vac single-phase (or 110 Vac dual-live lines)
	Frequency	45 to 66 Hz, rated: 50/60 Hz
	Maximum Input Current	≤ 17 A
	Power Factor	≥ 0.99 (> 50% load at 230 Vac)
	THD	≤ 5% (> 50% load at 230 Vac)
Output Feature	Efficiency	> 95% (30% to 100% load) > 96% Max
	Output Voltage	42 to 58 Vdc, rated voltage: 53.5 Vdc
	Output Power	3000W (176 to 300 Vac )
	Ripple and Noise	< 200 mV pk-pk, 20 M bandwidth, < 2 mV rms psophometric
	Hold-up Time	> 10 mS at 3000 W , output voltage > 42 V
	Output Regulated Voltage Precision	≤ 0.6% Vo from no load to full load
	Current Share	±5% output rated current from 10% to 100% load
Environmental Specifications	Operating Temperature	-40 °C to +75 °C (non-derating below 55 °C), ETS EN 300-019
	Storage Temperature	-40 °C to +75 °C; ETS EN 300-019
	Relative Humidity	5% to 95% (non-condensing), ETS EN 300-019
	Altitude Range	≤ 4000 m (If the altitude is within the range of 3000 m to 4000 m, the maximum operating temperature decreases by 1°C as the altitude increases by 200 m)
Protection	Input Overvoltage Protection	Protection point: > 300 Vac
	Input Under-voltage Protection	Protection point: < 80 Vac
	Output Over-voltage Protection	56 to 60 Vdc (can be set by monitoring unit)
	Output Short Circuit Protection	A long term short circuit is allowed. After the fault is rectified, the rectifier will restore automatically
	Over-temperature Protection	Protection point: ≥ 80 °C
Reliability	MTBF	≥ 500,000 hours (Telcordia SR-332 issue2 Method 1 at 25 °C)
Audible Noises	Specification	≤ 55dB (40 °C, full load); sound presure@1m distance, ISO3744
Safety/EMC/ Lightning Protection	Safety Certification	Passed TUV, CE, UL, FCC certifications; got the CB certificate; complies with UL60950-1, IEC60950-1, EN60950-1, CAN/CSA C22.2 No. 60950 -1
	Isolation	Input to output: 4242 Vdc; input to earth: 2121 Vdc; output to earth: 707 Vdc
	EMC	EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, ETSI EN300 386, ETSI EN301489, ITU-T K.20, FCC CFR47 Part 15 Subpart B:2012
	Lightening protection	Common model (input to earth) / differential model (input to input): 5KA (8/20uS, ITU-T K.44)

Copyright © Huawei Technologies Co., Ltd. 2016. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

#### General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

**HUAWEI TECHNOLOGIES CO., LTD.**

Huawei Industrial Base

Bantian Longgang

Shenzhen 518129, P.R. China

Tel: +86-755-28780808

www.huawei.com