

OptiXstar P813E Datasheet

Enterprise-Level Routing Gateway ONU

Product Overview

The OptiXstar P813E is an ONU designed for scenarios such as enterprise campus and video backhaul. It provides 8 GE ports wiht PoE/PoE+ to provide high-quality voice, data, and HD video services.

Date: 2019-10-30



Product Highlights

- 802.1x and IPv6/IPv4 firewalls ensure device access security and network security.
- Supports XGS-PON uplink access.
- The PoE/PoE+ function supports flexible power supply.
- Features high reliability, type B dual-homing service protection.

Technical Specifications

Dimensions (WxDxH)	220mm x 150mm x 35mm (Without floor mat)	UNI	8*GE(PoE/PoE+)	
Weight	About 1030 g	Static power consumption	8 W	
Operating temperature	-5°C to +45°C	Maximum power consumption	12 W (POE port without PD) 143 W (POE port with PD having the maximum power consumption)	
Operating humidity	5%RH to 95%RH (non- condensing)	Maximum PoE output power	Gross power 120W (up to 30W for one GE port)	

OptiXstar P813E Datasheet

Power adapter input	100V to 240V AC,50/60Hz	Surge protection specifications	GE: common mode 4 kV; differential mode 0.5 kV. AC power: common mode 6 kV; differential mode 6 kV
System power supply	56V DC,2.6A	Installation mode	Support indoor desktop installation, wall mounting, or network box installation.
NNI	XGS-PON	-	-

Port Parameters

SPF	GE	
XGS-PON optical module, port type: SC/UPCXGS-PON:	PoE and PoE+, complying with IEEE 802.3af and IEEE 802.3at	
- Class N1/N2;	Port type:RJ-45	
 Receiver sensitivity:-28dBm; 	Auto ports speed(10/100/1000 Mbit/s)	
 Overload optical power: -9dBm; 	Auto-MDI/MDIX	
 Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s 	Configuration of the number of MAC addresses learned	
Type B single-homing	VLAN transparent transmission/VLAN filtering	
Type B dual-homing (supported in Layer 2 forwarding)		

Function List

Automatic Service Provisioning	Smart O&M	Layer 3 Features	Security	
 Authenticati on exemption XML/OMCI/ TR069 	 XML/Web UI Rogue ONT detection and self-regulation Ring network detection/PPPoE/DHCP simulation testing 	 Default/Static/Policy/Service routes VLAN binding ALG/UPnP/ARP DDNS/DMZ/DNS/NAPT PPPoE/Static IP/DHCP Port mapping/Port trigger IPv6 	 802.1x IPv6/IPv4 firewalls Filtering based on MAC/IP/URL DoS/ARP anti-attacks Static MAC address binding 	
Multicast	QoS	Layer 2 Management	Device access control Web session number restriction	
 IGMP v2/v3 snooping Dynamic controllable multicast IGMP proxy MLDv1/ML Dv2 snooping 	 Ethernet port rate limitation 802.1p priority SP/WRR/SP+WRR 	 DHCP Option82 PITP BPDU transparent transmission LLDP/LLDP-MED 		

OptiXstar P813E Datasheet

Copyright © Huawei Technologies Co., Ltd. 2019. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

W HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address:Huawei Industrial Base Bantian, Longgang Shenzhen 518129 People's Republic of China

Website:www.huawei.com

3 OptiXstar P813E Datasheet